

UV sterilizer suitable for water disinfection thanks to the UV-C radiation with wavelength of 254nm. Equipped with a low pressure mercury lamp of 30W electrical power, contained in high quality quartz sleeve and controlled by digital electronic control unit with LCD display

REACTOR

Max flow rate:	1,5 m ³ /hr – 6,60 GPM initial Dose 30.000 μWsec/cm ² 1,2 m ³ /hr – 5,28 GPM initial Dose 40.000 μWsec/cm ²
UV lamp:	1x30W, 9.000 hr lifespan
Dimension:	Height 520 mm - Ø 60,30 mm
Form factor:	“C” chamber
Working position:	Vertical / Horizontal
Connection:	¾” threaded male
Max working pressure:	10 Bar standard
Material:	AISI 304 – EN 1.4301 (AISI 316 – EN 1.4401 as optional)
Compliance:	EN 10217-7



CONTROL UNIT

Type:	Digital electronic control unit UV ³
Dimension:	180 x 180 x 90 mm
Lamp control:	Lamp monitoring and lamp end of life Total hours count for plant and partial resettable lamp life count Change lamp counter
System features:	ON/OFF remote command Solenoid valve managing (powered relay 230 Vac) Stand By command via “OK” button
Alarm:	Lamp failure Lamp end of life Low UV radiation (sensor only) High temperature (sensor only)
Relay:	Powered relay 230 Vac Free contact relay
Power connection:	Power cord 1,5 mt
Lamp cable:	1,5 mt included
Power supply:	230 Vac ± 10%
Electrical absorption:	30W
Protection degree:	IP 54
EMC compliance:	EN 55022 ; EN 61000-3-2 ; EN 61000-4 ; EN 61347-1/A1 ; EN 61195 ; 2014/30/EU ; 2014/35/EU



OPTIONS

Reactor:	Client logo printed AISI 316 – EN 1.4401 Radiation and temperature sensor
Power supply:	Client logo on display at power on Protection degree IP 65



PACKAGING

Dimension:	20 x 10 x 75 cm (W x H x D)
Weight:	3,0 Kg
EPAL packages quantity:	48 pcs